

# Dekso 1 Ultramat

## Product properties

Ultramat 100 % acrylic wall and ceiling paint. Recommended for premises with high functional and special aesthetic requirements that are exposed to some dirt and wear and tear.

- Wall and ceiling paint
- Ultramat
- Robust surface



## Labelling



## Product use

Living rooms, corridors, entrance areas, offices, kitchens, clinics, retail shops and stairways.  
Concrete, lightweight concrete, plaster, bricks, gypsumboards, fiber plaster, cement fiber boards, cement particle boards.

## Substrate

Must be clean, dry, solid and suitable for surface treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.  
Remove dirt, grime, grease and chalking materials with Fluren 37.  
Water blotches or surfaces stained by nicotine or soot must be cleaned with Fluren 49 and treated with Stop Primer.  
Hard, smooth surfaces should be sanded matt and painted with Fix Primer as required.  
Cracks, unevenness and holes must be spackled.  
Absorbent and porous substrates must be primed with Flügger Sealer.  
Priming is done with Wall Primer Perform or Wall Primer Pro.  
Apply 1-2 times. Some colours require an extra treatment.

## Application

Brush, roller or spray.  
Decide your choice of tool/utensil depending on the finish.  
Apply wet on wet and finish by brushing/rolling in the same direction.  
Always use the same batch number on contiguous/unbroken surfaces.  
Differences in surface structure can result in colour deviation.  
Cold/heat can affect the viscosity of the material.  
Material temperature for spray painting, min. 12°C.  
Condensation during drying/curing must not occur.  
Cold and increased humidity extends drying time, full curing and recoat interval.  
Increased temperature and low atmospheric humidity reduce drying time and full curing.  
Always perform a test treatment for a check and acceptance of adhesion and result.

## Expected result

Ultramatt surface with a subdued even structure and uniform finish.  
Withstands cleaning including spot cleaning with mild detergents without abrasives, soft brush, water and cloth.  
Strong especially dark shades are more delicate than light by wear and touch.  
Chalking from strong shades due to excess pigment may occur.  
Does not block strike-through from knots or water-soluble colourants, water stains and nicotine.  
Exercise care in loading the surface until the paint is fully cured.

## Environmental information

Remove as much paint as possible before cleaning. Bring remains of fluent paint to the local recycling centre.  
Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

**Storage:** Cool, frost free and tightly closed

## Supplementary Info

For this product there is issued an: [Environmental Product Declaration](#)

## Technical Data

Product Type	100% acrylic paint
Gloss	Ultra Matte;Full Matte;1
Density (kgs/l)	1.42
Solids Weight %	59
Solids Vol. %	41
Nominal spreading rate (m <sup>2</sup> /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 1
Fire Class	B-s1, d0
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water

### Current TDS Version

March 2024

### Replaces TDS Version

November 2023